

07. 11. 2000

(52)

TS 5549 PCTNEW SET OF CLAIMSSUBA₁ >

5

1. Process for the catalytic dewaxing of a hydrocarbon oil feed including waxy molecules and more than 500 ppmw of sulphur or sulphur containing compounds by contacting the oil feed under catalytic dewaxing conditions with a catalyst composition comprising a Group VIII metal hydrogenation component, dealuminated aluminosilicate zeolite crystallites, wherein the aluminosilicate zeolite crystallites have a Constraint Index of between 2 and 12, and a low acidity refractory oxide binder material which is essentially free of alumina.

2. Process according to claim 1, wherein the oil feed comprises more than 750 ppmw of sulphur or sulphur containing compounds.

3. Process according to any one of claims 1-2, wherein the oil feed comprises more than 10 ppmw of nitrogen or nitrogen containing compounds.

4. Process according to any one of claims 1-3, wherein the hydrogenation component is platinum, palladium or nickel.

20

5. Process according to any one of claims 1-4, wherein the low acidity binder is silica.

6. Process according to any one of claims 1-5, wherein the aluminosilicate zeolite crystallites is of the MFI type.

25

7. Process according to any one of claims 1-6, wherein the dealuminated aluminosilicate zeolite crystallites are obtained by contacting the zeolite crystallites with an aqueous solution of a fluorosilicate salt wherein the fluorosilicate salt is represented by the formula:

(A)₂/bSiF₆

wherein 'A' is a metallic or non-metallic cation other than H⁺ having the valence 'b', preferably ammonium.

5 8. Process according to any one of claims 7, wherein an extrudate of the aluminosilicate zeolite crystallites and the low acidity binder is contacted with the aqueous solution of the fluorosilicate salt.

10 9. Process according to any one of claims 1-8, wherein the oil feed is a solvent extracted waxy raffinate.

10. Process according to any one of claims 1-8, wherein the oil feed is a gas oil.

15 11. Process according to any one of claims 1-8, wherein the oil feed is a hydrocracker feedstock and wherein the dewaxed oil is subsequently subjected to a hydrotreating step before being subjected to a hydrocracker process step in which step primarily middle distillates are prepared.

20 12. Method for retrofitting a process for preparing lubricating base oils wherein an existing solvent dewaxing step is replaced by a catalytic dewaxing process according to any one of claims 1 to 9.

09855022-051604
T09T50-22995860

ADD
A₃ >

MCS31/TS5549PCT

AMENDED SHEET